# **Technical Data Sheet**

Nitrocellulose (Hacocell / Hacoplast)



Type Norm Type of solubility

27 E Ester Alcohol Special/Medium alcohol


### **Properties/Application**

Medium viscosity NC for the manufacture of lacquers and special printing inks


Main application fields: combination lacquers, sealers, spray lacquers, wood lacquers

#### **Product specification** Viscosity [mPa s] 400 ± 25 Solvents for nitrocellulose according to ISO 14446 11,8 - 12,4 [%] Nitrogen NC-V006A Colour [APHA-selekt] ≤ 300 genuine solvent [Gardner] ≤ 2,5 NC-V009A/C latent solvent diluting agent (non-solvent)

### **Product variants**



## Supply form



Concerning security measures at handling and danger instructions for storing and transporting, please, refer to the information sheet M 037 12/93 of the Employers/Employee's Liability Insurance Association of the Chemical Industry and also to our Material Safety Data Sheet and our Transport Safety Data Sheet. The information in this publication, and any subsequent advice of a technical nature given either by word of mouth or in writing, is based on our know-how and experience. It is however the responsibility of the customer to verify whether our products are suitable for the range of application in each individual case, and to have due regard to rights of Third parties which may be in contrast with the processing or any other kind of use. No claims whatever can be brought against us on the basis on the information contained in this publication, or of any advice of a technical nature which may subsequently be given. This publication become void once a re-edition will be published. (edition 07/2013)